

AAFA silencers - clean air with baffle L = 2000





AAFA silencers - clean air with baffle L = 2000
AAFA silencers are designed to reduce the sound in ducting or in the workshop for use in overpressure, under-pressure and pressureless systems.

The silencers are made of galvanized sheet metal with sound absorbing material applied on the inside.

Material
Sendzimir galvanized
100 mm soundproofing material

Type
Rolled stitch-welded sheets with 6 mm edges for lock rings.

Options
- Other diameters
- Other lengths
- Other sheet thickness
- With perforated sheet metal plate for loaded air
- With Tedlar foil for moist medium
- Stainless steel (AISI 304)
- Painted version
- Other types of edges or connections, see ‘edges and connections’


Loaded air version

Ø	Model	Ø d1	Ø d2	L1	L2	L3	s	Weight
		mm	mm	mm	mm	mm	mm	kg
225	AAFA000265	225	425	2000	50	100	0.88	38,40
250	AAFA000266	250	450	2000	50	100	0.88	40,80
275	AAFA000267	275	475	2000	50	100	0.88	43,20
300	AAFA000268	300	600	2000	50	100	0.88	45,60
315	AAFA000269	315	515	2000	50	100	0.88	53,00
350	AAFA000270	350	550	2000	50	100	0.88	58,40
400	AAFA000271	400	600	2000	50	100	0.88	62,80
450	AAFA000272	450	650	2000	50	100	0.88	69,20
500	AAFA000273	500	700	2000	50	100	0.88	80,00
550	AAFA000274	550	750	2000	50	100	0.88	80,60
600	AAFA000275	600	800	2000	50	100	0.88	87,00
630	AAFA000276	630	830	2000	50	100	0.88	94,40
650	AAFA000277	650	850	2000	50	100	0.88	98,80
700	AAFA000398	700	900	2000	50	100	0.88	117.20
750	AAFA000399	750	950	2000	50	100	0.88	131.92
800	AAFA000400	800	1000	2000	50	100	0.88	141.60
850	AAFA000401	850	1050	2000	50	100	0.88	151.32
900	AAFA000402	900	1100	2000	50	100	0.88	157.00
950	AAFA000403	950	1150	2000	50	100	0.88	169.48
1000	AAFA000404	1000	1200	2000	50	100	0.88	182.16